

CONSTANTS, CONVERSIONS, and CHARACTERS

DECIMAL MULTIPLIER PREFIXES

Prefix	Symbol	Multiplier
exa	E	10 ¹⁸
peta	P	10 ¹⁵
tera	T	10 ¹²
giga	G	10 ⁹
mega	M	10 ⁶
kilo	k	10 ³
hecto	h	10 ²
deka	da	10 ¹
deci	d	10 ⁻¹
centi	c	10 ⁻²
milli	m	10 ⁻³
micro	μ	10 ⁻⁶
nano	n	10 ⁻⁹
pico	p	10 ⁻¹²
femto	f	10 ⁻¹⁵
atto	a	10 ⁻¹⁸

EQUIVALENCY SYMBOLS

Symbol	Meaning
=	Proportional
≈	Roughly equivalent
≈	Approximately
≈	Nearly equal
=	Equal
=	Identical to, defined as
=	Not equal
>>	Much greater than
>	Greater than
>=	Greater than or equal to
<<	Much less than
<	Less than
<=	Less than or equal to
∴	Therefore
°	Degrees
'	Minutes or feet
"	Seconds or inches

UNITS OF LENGTH

1 inch (in)	= 2.54 centimeters (cm)
1 foot (ft)	= 30.48 cm = 0.3048 m
1 yard (yd)	= 0.9144 meter
1 meter (m)	= 39.37 inches
1 kilometer (km)	= 0.54 nautical mile
	= 0.62 statute mile
	= 1093.6 yards
	= 3280.8 feet
1 statute mile	= 0.87 nautical mile
(sm or stat. mile)	= 1.61 kilometers
	= 1760 yards
	= 5280 feet
1 nautical mile	= 1.15 statute miles
(nm or naut. mile)	= 1.852 kilometers
	= 2025 yards
	= 6076 feet
1 furlong	= 1/8 mi (220 yds)

UNITS OF SPEED

1 foot/sec (fps)	= 0.59 knot (kt)*
	= 0.68 stat. mph
	= 1.1 kilometers/hr
1000 fps	= 600 knots
1 kilometer/hr	= 0.54 knot
(km/hr)	= 0.62 stat. mph
	= 0.91 ft/sec
1 mile/hr (stat.)	= 0.87 knot
(mph)	= 1.61 kilometers/hr
	= 1.47 ft/sec
1 knot*	= 1.15 stat. mph
	= 1.69 feet/sec
	= 1.85 kilometers/hr
	= 0.515 m/sec

*A knot is 1 nautical mile per hour.

UNITS OF VOLUME

1 gallon	= 3.78 liters
	= 231 cubic inches
	= 0.1335 cubic ft
	= 4 quarts
	= 8 pints
1 fl ounce	= 29.57 cubic centimeter (cc)
	or milliliters (ml)
1 in ³	= 16.387 cc

UNITS OF AREA

1 sq meter	= 10.76 sq ft
1 sq in	= 645 sq millimeters (mm)
	= 1,000,000 sq mil
1 mil	= 0.001 inch
1 acre	= 43,560 sq ft

UNITS OF WEIGHT

1 kilogram (kg)	= 2.2 pounds (lbs)
1 pound	= 0.45 Kg
	= 16 ounce (oz)
1 oz	= 437.5 grains
1 carat	= 200 mg
1 stone (U.K.)	= 6.36 kg

NOTE: These are the U.S. customary (avoirdupois) equivalents, the troy or apothecary system of equivalent, which differ markedly, was used long ago by pharmacists.

UNITS OF POWER / ENERGY

1 H.P.	= 33,000 ft-lbs/min
	= 550 ft-lbs/sec
	= 746 Watts
	= 2,545 BTU/hr
(BTU = British Thermal Unit)	
1 BTU	= 1055 Joules
	= 778 ft-lbs
	= 0.293 Watt-hrs

SCALES

OCTAVES
 "N" Octaves = Freq to Freq x 2^N
 i.e. One octave would be 2 to 4 GHz
 Two Octaves would be 2 to 8 GHz
 Three octaves would be 2 to 16 GHz

DECADES

"N" Decades = Freq to Freq x 10^N
 i.e. One decade would be 1 to 10 MHz
 Two decades would be 1 to 100 MHz
 Three decades would be 1 to 1000 MHz

TEMPERATURE CONVERSIONS

*F = (9/5)*C + 32
C = (5/9)(F - 32)
*K = *C + 273.16
F = (9/5)(K - 273) + 32
*C = *K - 273.16
K = (5/9)(F - 32) + 273

UNITS OF TIME

1 year	= 365.2 days
1 fortnight	= 14 nights (2 weeks)
1 century	= 100 years
1 millennium	= 1,000 years

NUMBERS

1 decade	= 10
1 Score	= 20
1 Billion	= 1 x 10 ⁹ (U.S.)
	(thousand million)
	= 1 x 10 ¹² (U.K.)

RULE OF THUMB FOR ESTIMATING DISTANCE TO LIGHTNING / EXPLOSION:

km - Divide 3 into the number of seconds which have elapsed between seeing the flash and hearing the noise.
 miles - Multiply 0.2 times the number of seconds which have elapsed between seeing the flash and hearing the noise.
 Note: Sound vibrations cause a change of density and pressure within a media, while electromagnetic waves do not. An audio tone won't travel through a vacuum but can travel at 1100 ft/sec through air. When picked up by a microphone and used to modulate an EM signal, the modulation will travel at the speed of light.

Physical Constant	Quoted Value	S*	SI unit	Symbol
Avogadro constant	6.0221367 x 10 ²³	36	mol ⁻¹	N _A
Bohr magneton	9.2740154 x 10 ⁻²⁴	31	J·T ⁻¹	μ _B
Boltzmann constant	1.380658 x 10 ⁻²³	12	J·K ⁻¹	k=(R·N _A)
Electron charge	1.60217733 x 10 ⁻¹⁹	49	C	-e
Electron specific charge	-1.75881962 x 10 ¹¹	53	C·kg ⁻¹	-e/m _e
Electron rest mass	9.1093897 x 10 ⁻³¹	54	kg	m _e
Faraday constant	9.6485309 x 10 ⁴	29	C·mol ⁻¹	F
Gravity (Standard Acceleration)	9.80665 or 32.174	0	m/sec ² ft/sec ²	g
Josephson frequency to voltage ratio	4.8359767 x 10 ¹⁴	0	Hz·V ⁻¹	2e/hg
Magnetic flux quantum	2.06783461 x 10 ⁻¹⁵	61	Wb	Φ ₀
Molar gas constant	8.314510	70	J·mol ⁻¹ ·K ⁻¹	R
Natural logarithm base	= 2.71828	-	dimensionless	e
Newtonian gravitational constant	6.67259 x 10 ⁻¹¹	85	m ³ ·kg ⁻¹ ·s ⁻²	G or K
Permeability of vacuum	4π x 10 ⁻⁷	d	H/m	μ ₀
Permittivity of vacuum	= 8.8541878 x 10 ⁻¹²	d	F/m	ε ₀
Pi	= 3.141592654	-	dimensionless	π
Planck constant	6.62659 x 10 ⁻³⁴	40	J·s	h
Planck constant/2π	1.05457266 x 10 ⁻³⁴	63	J·s	ħ=(h/2π)
Quantum of circulation	3.63694807 x 10 ⁻⁴	33	J·s·kg ⁻¹	h/2m _e
Radius of earth (Equatorial)	6.378 x 10 ⁶ or 3963	-	m miles	-
Rydberg constant	1.0973731534 x 10 ⁷	13	m ⁻¹	R _y
Speed of light	2.9979246 x 10 ⁸	1	m·s ⁻¹	c
Speed of sound (dry air @ std press & temp)	331.4	-	m·s ⁻¹	-
Standard volume of ideal gas	22.41410 x 10 ⁻³	19	m ³ ·mol ⁻¹	V _m
Stefan-Boltzmann constant	5.67051 x 10 ⁻⁸	19	W·K ⁻⁴ ·m ⁻²	σ

* 5 is the one-standard-deviation uncertainty in the last units of the value, d is a defined value.
 (A standard deviation is the square root of the mean of the sum of the squares of the possible deviations)

Physical Constant	Quoted Value	S*	SI unit	Symbol
Avogadro constant	6.0221367 x 10 ²³	36	mol ⁻¹	N _A
Bohr magneton	9.2740154 x 10 ⁻²⁴	31	J·T ⁻¹	μ _B
Boltzmann constant	1.380658 x 10 ⁻²³	12	J·K ⁻¹	k=(R·N _A)
Electron charge	1.60217733 x 10 ⁻¹⁹	49	C	-e
Electron specific charge	-1.75881962 x 10 ¹¹	53	C·kg ⁻¹	-e/m _e
Electron rest mass	9.1093897 x 10 ⁻³¹	54	kg	m _e
Faraday constant	9.6485309 x 10 ⁴	29	C·mol ⁻¹	F
Gravity (Standard Acceleration)	9.80665 or 32.174	0	m/sec ² ft/sec ²	g
Josephson frequency to voltage ratio	4.8359767 x 10 ¹⁴	0	Hz·V ⁻¹	2e/hg
Magnetic flux quantum	2.06783461 x 10 ⁻¹⁵	61	Wb	Φ ₀
Molar gas constant	8.314510	70	J·mol ⁻¹ ·K ⁻¹	R
Natural logarithm base	= 2.71828	-	dimensionless	e
Newtonian gravitational constant	6.67259 x 10 ⁻¹¹	85	m ³ ·kg ⁻¹ ·s ⁻²	G or K
Permeability of vacuum	4π x 10 ⁻⁷	d	H/m	μ ₀
Permittivity of vacuum	= 8.8541878 x 10 ⁻¹²	d	F/m	ε ₀
Pi	= 3.141592654	-	dimensionless	π
Planck constant	6.62659 x 10 ⁻³⁴	40	J·s	h
Planck constant/2π	1.05457266 x 10 ⁻³⁴	63	J·s	ħ=(h/2π)
Quantum of circulation	3.63694807 x 10 ⁻⁴	33	J·s·kg ⁻¹	h/2m _e
Radius of earth (Equatorial)	6.378 x 10 ⁶ or 3963	-	m miles	-
Rydberg constant	1.0973731534 x 10 ⁷	13	m ⁻¹	R _y
Speed of light	2.9979246 x 10 ⁸	1	m·s ⁻¹	c
Speed of sound (dry air @ std press & temp)	331.4	-	m·s ⁻¹	-
Standard volume of ideal gas	22.41410 x 10 ⁻³	19	m ³ ·mol ⁻¹	V _m
Stefan-Boltzmann constant	5.67051 x 10 ⁻⁸	19	W·K ⁻⁴ ·m ⁻²	σ

* 5 is the one-standard-deviation uncertainty in the last units of the value, d is a defined value.
 (A standard deviation is the square root of the mean of the sum of the squares of the possible deviations)

GREEK ALPHABET

Case	Greek Alphabet Name		English Equivalent
	Upper	Lower	
A	Α	α	alpha
B	Β	β	beta
Γ	Γ	γ	gamma
Δ	Δ	δ	delta
E	Ε	ε	epsilon
Z	Ζ	ζ	zeta
H	Η	η	eta
Θ	Θ	θ	theta
I	Ι	ι	iota
K	Κ	κ	kappa
Λ	Λ	λ	lambda
M	Μ	μ	mu

Case	Greek Alphabet Name		English Equivalent
	Upper	Lower	
N	Ν	ν	nu
Ξ	Ξ	ξ	xi
O	Ο	ο	omicron
Π	Π	π	pi
P	Ρ	ρ	rho
Σ	Σ	σ	sigma
T	Τ	τ	tau
Υ	Υ	υ	upsilon
Φ	Φ	φ	phi
X	Χ	χ	chi
Ψ	Ψ	ψ	psi
Ω	Ω	ω	omega

LETTERS FROM THE GREEK ALPHABET COMMONLY USED AS SYMBOLS

Symbol	Name	Use
α	alpha	space loss, angular acceleration, or absorptance
β	beta	3 dB bandwidth or angular field of view [radians]
Γ	Gamma	reflection coefficient
γ	gamma	electric conductivity, surface tension, missile velocity vector angle, or gamma ray
Δ	Delta	small change or difference
δ	delta	delay, control forces and moments and permissivity [farads/meter]
ε	epsilon	emissivity [dielectric constant] or permittivity [farads/meter]
η	eta	efficiency or antenna aperture efficiency
θ	Theta	angle of lead or lag between current and voltage
θ or θ	theta	azimuth angle, bank angle, or angular displacement
λ	Lambda	acoustic wavelength or rate of energy loss from a thermocouple
λ	lambda	wavelength or Poisson Load Factor
μ	mu	micro 10 ⁻⁶ [micron], permeability [henrys/meter], or extinction coefficient [optical region]
ν	nu	frequency
π	pi	3.141592654+
ρ	rho	charge mass density, resistivity [ohm-meter], VSWR, or reflectance
σ	Sigma	algebraic sum
σ	sigma	radar cross section [RCS], Conductivity [1/ohm-meter], or Stefan-Boltzmann constant
T	Tau	VSWR reflection coefficient
τ	tau	pulse width, atmospheric transmission, or torque
φ	Phi	magnetic electrical flux, radiant power [optical region], or Wavelet's smooth function [low pass filter]
φ or φ	phi	phase angle, angle of bank, or beam divergence [optical region]
ψ	Psi	time-dependent wave function or Wavelet's detail function [high pass filter]
ψ	psi	time-independent wave function, phase change, or flux linkage [webber]
Ω	Omega	Ohms [resistance] or solid angle [optical region]. Note: inverted symbol is conductance [mhos]
ω	omega	carrier frequency in radians per second

IRLANGLES

Angles: A + B + C = 180°
 c² = a² + b² - 2ab cos C
 Area = 1/2 bh = 1/2 ac sin B
 c = √(a² + b²)

SPHERE

Surface area = 4πr²
 Volume = 4/3 πr³
 Cross Section (circle)
 Area = πr²
 Circumference (c) = 2πr

DERIVATIVES

Assume: a = fixed real #; u, v, w are functions of x
 d(a)/dx = 0 ; d(sin u)/dx = du(cos u)/dx
 d(x)/dx = 1 ; d(cos v)/dx = -dv(sin v)/dx
 d(uvw)/dx = uvw'/dx + vwdv'/dx + uwdv'/dx + ...etc

INTEGRALS

Note: All integrals should have a constant of integration added
 Assume: a = fixed real #; u, v, w are functions of x
 ∫ dx = ax and ∫ a f(x) dx = a ∫ f(x) dx
 ∫ (u+v) dx = ∫ u dx + ∫ v dx ; ∫ e^{ax} dx = e^{ax}/a
 ∫ (sin ax) dx = -(cos ax)/a ; ∫ (cos ax) dx = (sin ax)/a

